

# PERFITHERM

## Scraped Surface Heat Exchanger



CAPACITIES

**100 kg/hr to 10.000 kg/hr**




**PERFIPROCESS**

by PERFINOX | [www.perfinox.pt](http://www.perfinox.pt)

## CONCEPT

Scraped Surface Heat Exchanger, vertical, with double jacket for a maximum surface and efficient exchange.

The system combines the advantages of the tubular heat exchanger, with a slow and gentle sitting system, equipped with scrappers.



## ADVANTAGES

- Gentle product handling
- Vertical design, compact equipment
- High cleaning and safety
- Easy maintenance
- Designed for CIP and SIP

## CAPACITY

From 100 kg/hr to 10.000 kg/hr, with exchange surfaces from 0.5 m<sup>2</sup> to 7.0 m<sup>2</sup>

## APPLICATIONS

- Mayonnaise
- Ketchup
- Sauces
- Soups
- Creams
- Ready meal sauces
- Pates
- Fruit preparations
- Dairy concentrates
- Humus



## PROCESSES

- Heating
- Deep-cooling
- Aseptic cooling
- Crystallization
- Sterilization
- Pasteurization
- Gelling

## OPTIONS

- Temperature probes (inlet/outlet)
- Scrappers on the lid
- Double mechanical seal
- Jacketed product outlet
- "Ready to work" pack, with modulating valve, traps, shutoff valves and accessories
- Motor shroud
- Skid mounting, including control system

PERFINOX - Indústria Metalúrgica, S.A.  
Z. Ind. Lameiradas, Lote 1  
Mansores - 4540 - 423 Arouca  
PORTUGAL  
[www.perfinox.pt](http://www.perfinox.pt)

[perfinox@perfinox.pt](mailto:perfinox@perfinox.pt)  
(+351) 256 928 145  
(+351) 256 928 150  
[www.linkedin.com/company/perfinox](https://www.linkedin.com/company/perfinox)